


SIVACON S4, панель-заглушка 3VL2-3, до 250 A, 4-пол., стац. втычной фронтальный поворотный привод моторизованный привод, блок ВДТ, В: 500 мм, Ш: 800 мм



версия	
исполнение изделия	VL160, VL250
класс защиты	
степень защиты IP	IP30
пригодность к использованию / для наружного использования	нет
появление	
цвет	светло-серый
характеристика изделия / встраиваемая приточная/вытяжная вентиляция	нет
Механическая конструкция	
высота	500 mm
ширина	800 mm
глубина	10 mm
масса нетто	3 440 g
материал	стальной лист
General Product Approval	
Declaration of Conformity	

[Confirmation](#)



[Miscellaneous](#)



EG-Konf.

Declaration of Conformity	other
---------------------------	-------

[Miscellaneous](#)

[UK Declaration of Conformity](#)

[Miscellaneous](#)

Дополнительная информация

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/ru/ru/Catalog/product?mlfb=8PQ2050-8BA11>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/ru/ps/8PQ2050-8BA11>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8PQ2050-8BA11

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



