

# PAFL21/GR/50M



LIGHT WGT GRY NYL COND NC21 50M



## General Information

|                       |  |
|-----------------------|--|
| Extended Product Type | PAFL21/GR/50M  |
| Product ID            | 7TCA296000R2128  |
| EAN                   | 5020963002274  |
| Catalog Description   | LIGHT WGT GRY NYL COND NC21 50M  |
| Long Description      | Lightweight Conduit, Nominal Conduit Size 21mm, NW Conduit Size 17, Fine Conduit Pitch, Outside Diameter 21.2mm, Inside Diameter 16.8mm, Static Bend Radius 45mm, Reel Length 50 Meters, Polyamide (Nylon) 6, Grey |

## Ordering

|                       |               |
|-----------------------|---------------|
| EAN                   | 5020963002274 |
| Customs Tariff Number | 3926909990    |

## Dimensions

|                    |                     |
|--------------------|---------------------|
| Product Net Weight | 6.17 lb<br>2.798 kg |
|--------------------|---------------------|

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 2 Units          | 1 piece       |
| Package Level 2 Width          | 1 in<br>25 mm |
| Package Level 2 Height         | 1 in<br>25 mm |
| Package Level 2 Depth / Length | 1 in<br>25 mm |

## Additional Information

|                 |  |
|-----------------|--|
| Application     | Indoors / Outdoors - Light Industrial, Buildings & Machinery |
| Brand / Label   | Adaptaflex   |
| Color           | Gray   |
| Flexibility     | High   |
| Inside Diameter | 16.8 mm  |
| Material        | Polyamide/Nylon 6  |

|                     |  |
|---------------------|--|
| Nominal Size        | 21 mm                                    |
| Number of Batteries | 0  |
| Outside Diameter    | 21.2 mm                                  |
| Product Name        | FLEXIBLE CONDUIT, NYLON                  |
| Product Type        | Lightweight Conduit with Fine Pitch      |
| Radius              | 45 mm                                    |
| Special Functions   | Very High UV Protection and Fatigue Life |
| UPC                 | 786210268545                             |

---

### Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | PAFL21/GR/50M   |
| Declaration of Conformity - CE    | 9AKK107492A9618 |
| Instructions and Manuals          | PAFL21/GR/50M   |

---

### Classifications

|                                    |                                    |
|------------------------------------|------------------------------------|
| ETIM 6                             | EC001175 - Corrugated plastic hose |
| ETIM 7                             | EC001175 - Corrugated plastic hose |
| UNSPSC                             | 39131706                           |
| WEEE Category                      | Product Not in WEEE Scope          |
| IDEA Granular Category Code (IGCC) | 5535 >> Electrical conduit         |

---

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

