

SPL25/GR/50M



50M X SPL25/GRCOND



General Information

Extended Product Type	SPL25/GR/50M
Product ID	7TCA296030R0203
EAN	5020963779268
Catalog Description	50M X SPL25/GRCOND
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 25mm, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 50 Meters, PVC Covering with Galvanised Steel Core, Grey

Ordering

EAN	5020963779268
Customs Tariff Number	7412200035

Dimensions

Product Net Weight	56.99 lb 25.846 kg
--------------------	-----------------------

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Gray
Flexibility	Medium
Inside Diameter	21.0 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	3/4 in NC25

Number of Batteries	0
Outside Diameter	26.4 mm
Product Name	ADAPTAFLEX
Product Type	Oil Resistant Conduit
Radius	110 mm
UPC	786210275116

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL25/GR/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL25/GR/50M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

