

# SB20/25M



STEEL BRAIDED COND NC20 25M



## General Information

Extended Product Type	SB20/25M
Product ID	7TCA296040R0040
EAN	5020963001093
Catalog Description	STEEL BRAIDED COND NC20 25M
Long Description	Low Fire Hazard, High Flexibility, Covered Steel Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.5mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, Reel Length 25 Meters, Galvanised Steel Core and Overbraid

## Ordering

EAN	5020963001093
Customs Tariff Number	8307106000

## Dimensions

Product Net Weight	42.09 lb 19.088 kg
--------------------	-----------------------

## Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	37 in 940 mm
Package Level 2 Height	17 in 432 mm
Package Level 2 Depth / Length	17 in 432 mm

## Additional Information

Application	Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	16.9 mm
Material	Galvanized Steel Core and Overbraid
Nominal Size	1/2 in
Number of Batteries	0

Outside Diameter	21.5 mm
Product Name	flexible metal conduit
Product Type	Low Fire Hazard Conduit
Radius	45 mm
Special Functions	Very High UV Protection and High Fatigue Life
UPC	786210244273

---

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SB20/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SB20/25M

---

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

---

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

