










Reversing contactor assembly, AC-3, 4 kW 400 V, 24 V DC 3-pole,
Size S0 screw terminal electrical and mechanical interlock 2 NO
integrated

Certificates/approvals

| General Product Approval | | Declaration of Conformity | Test Certificates | Marine / Shipping |
|--|---|---|---|--|
|  CSA |  UL |  |  EG-Konf. | Special Test Certificate  ABS |

| Marine / Shipping | other |
|--|------------------------------|
|  BUREAU VERITAS  GL  LRS  RMRS  DNV-GL DNVGL.COM/AF | Confirmation |

| Railway |
|-------------------------------------|
| Vibration and Shock |

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA2323-8XB30-1BG4>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA2323-8XB30-1BG4>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RA2323-8XB30-1BG4>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA2323-8XB30-1BG4&lang=en

Characteristic: Tripping characteristics, I²t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RA2323-8XB30-1BG4/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RA2323-8XB30-1BG4&objecttype=14&gridview=view1>

last modified:

04/27/2018