

eliwell



Electric Automation
Automation specialists

Артикул ICP11J0350000

ICP11J0350000 ELIWELL ICPLUS 902 J/K
PT100 12V

Покупка от Electric Automation Network



ЭЛЕКТРОННЫЙ КОНТРОЛЬ 1 SET POINT (ТЕМПЕРАТУРА , ВЛАЖНОСТЬ, ДАВЛЕНИЕ И ДРУГИЕ ВЕЛИЧИНЫ)

ICPlus 902 controllers are one-step electronic devices used to control temperature. They are Compatible with TelevisSystem and with ModBus protocol monitoring systems.

Container PC+ABS UL94 V-0 plastic resin casing, polycarbonate display window, thermoplastic resin buttons

Operating temperature -5...55°C

Storage temperature -30...85°C

Ambient humidity for operation and storage 10...90% RH (non-condensing)

| | ICPLUS 902 NTC/PTC | ICPLUS 902 V/I | ICPLUS 902 TC (J/K) PT100 |
|---|---|--|---|
| Display range | probe NTC: -50,0...110,0° Cprobe PTC: -55,0...140,0°C | -99...100 * -99,9...100,0 *999...1000 * | зонд Pt100: -150...650°Cprobe TcJ: -40...750° Cprobe TcK: -40...1350°C |
| Дисплей | decimal point * 3 and a half digits + sign | decimal point * 3 and a half digits + sign | decimal point * 3 and a half digits + sign |
| Analogue inputs | 1 PTC или NTC * | 1 V-I (0...1B,0...5V,0...10V,0...20mA,4...20mA) * | 1 Pt100 или 1 TcJ/ TcK |
| Connections | TTL port for connection to USB Unicard, TelevisSystem and systems with ModBus protocol (Needs Bus Adapter) | TTL port for connection to USB Unicard, TelevisSystem and systems with ModBus protocol (Needs Bus Adapter) | TTL port for connection to USB Unicard, TelevisSystem and systems with ModBus protocol (Needs Bus Adapter) |
| Digital outputs | 1 SPDT 8(4) - 250Va | 1 SPDT 8(4) - 250Va | 1 SPDT 8(4) - 250Va |
| Measurement range | from -50 to 140 ° C | from -1999 to 1999 | from -150 to 1350 °C |
| Power supply | 12 B~, 24 B~ ,12...24 B~/12...36VC (°) ±10% 50/60Hz115 B~/230 B~ ±10% 50/60Hz | 12 B~, 24 B~,12...24 B~/12...36VC (°) ±10% 50/60Hz115 B~/230 B~ ±10% 50/60Hz | 12 B~, 24 B~ ,12...24 B~/12...36VC (°) ±10% 50/60Hz115 B~/230 B~ ±10% 50/60Hz |
| Размеры | 74 x 32 x 59 мм | 74 x 32 x 59 мм | 74 x 32 x 59 мм |
| * выбирается с помощью параметра | | | |

Характеристики

| | |
|-----------------------|-------------------------|
| Ссылка | ICP11J0350000 |
| Модель | IC PLUS 902 J/KPT100 12 |
| Реле | 1 |
| Copy Card | Если |
| Humidity Probe | Если |

Pressure Transducer

Если

Напряжение питания

12 в пер. Тока/в постоянного тока

Совместимость Кабельным Телевидением, LCD Телевизоро

Если (необходимо Bus Adapter)

Поддержка ModBus

Если (необходимо Bus Adapter)

Зонды

1 PT100 или ТСК/ТСJ

Формат

Панель 74x32

Напряжение Питания

12 в пер. Тока/в постоянного тока