



MT8052iP



MT8072iP



MT8106iP

Performance, Design, and Versatility

# MT8000iE · iP Series

# The Comparison of Software Features Between Different Models



Software Feature			
	iE Series		iP Series
Project & Firmware Size Limit	22.5MB		22.5MB
History Size Limit	16MB		64MB
Project Protection	●		●
Pictures/Shape Library Embedded in Project	●		●
PLC TAG Embedded in Project	●		●
e-Mail	●		
Enhanced Security Mode	●		●
VNC Server	●		●
Circular Trend Display	●		●
Combo Button	●		●
MQTT(Publisher / Subscriber)	●		
Operation Log	●		●
OPC UA Client	●		●
Picture Viewer	●		●
Recipe Database / Recipe View	●		●
VNC Viewer	●		
Watchdog	●		●
EasyAccess 2.0	Optional		Optional

iE Series : MT8051iE

iP Series : MT8052iP, MT8072iP, MT8106iP

# iE Series



Model		MT8051iE
Display	Display	4.3" TFT
	Resolution	480 x 272
	Brightness (cd/ m <sup>2</sup> )	400
	Contrast Ratio	500: 1
	Backlight Type	LED
	Backlight Life Time	>30,000 hrs.
	Colors	16.7M
	LCD Viewing Angle (T/B/L/R)	50/70/70/70
	Pixel Pitch (mm)	0.198(H) x 0.198(V)
	Touch Panel	Type
Accuracy		Active Area Length(X)±2%, Width(Y)±2%
Memory	Flash	128 MB
	RAM	128 MB
Processor		32-bit RISC 600MHz
I/O Port	USB Host	USB 2.0 x 1
	Ethernet	10/100 Base-T x 1
	COM Port	COM1: RS-232/RS-485 2W/4W COM3: RS-485 2W
RTC		Built-in
Power	Input Power	22~28VDC
	Power Isolation	Built-in
	Power Consumption	450mA@24VDC
	Voltage Resistance	500VAC (1 min.)
	Isolation Resistance	Exceed 50MΩ @ 500VDC
Specification	PCB Coating	Yes
	Enclosure	Plastic
	Dimensions WxHxD	128 x 102 x 32 mm
	Panel Cutout	119 x 93 mm
	Weight	Approx. 0.25 kg
	Mount	Panel mount
Environment	Protection Structure	UL Type 4X (indoor use only) / NEMA4 / IP65 Compliant Front Panel
	Storage Temperature	-20° ~ 60° C (-4° ~ 140° F)
	Operating Temperature	0° ~ 45° C (32° ~ 113° F)
	Relative Humidity	10% ~ 90% (non-condensing)
	Vibration Endurance	10 to 25Hz (X, Y, Z direction 2G 30 minutes)
Certificate	CE	CE marked
	UL	cULus Listed
Software	Weincloud	EasyAccess 2.0 (Optional)

# iP Series



Model		MT8052iP	MT8072iP	MT8106iP
Display	Display	4.3" TFT	7" TFT	10.1" WVA
	Resolution	480 x 272	800 x 480	1024 x 600
	Brightness (cd/ m <sup>2</sup> )	400	450	350
	Contrast Ratio	500: 1	500: 1	1000: 1
	Backlight Type	LED	LED	LED
	Backlight Life Time	>30,000 hrs.	>30,000 hrs.	50,000 hrs.
	Colors	16.7M	16.7M	16.7M
	LCD Viewing Angle (T/B/L/R)	50/70/70/70	60/70/70/70	89/89/89/89
	Pixel Pitch (mm)	0.198(H) x 0.198(V)	0.1926(H) x 0.179(V)	0.2175(H) x 0.2088(V)
	Touch Panel	Type	4-wire Resistive Type	4-wire Resistive Type
Accuracy		Active Area Length(X)±2%, Width(Y)±2%	Active Area Length(X)±2%, Width(Y)±2%	Active Area Length(X)±2%, Width(Y)±2%
Memory	Flash	256 MB	256 MB	256 MB
	RAM	128 MB	128 MB	128 MB
Processor		Dual-core RISC	Dual-core RISC	Dual-core RISC
I/O Port	USB Host	USB 2.0 x 1	USB 2.0 x 1	USB 2.0 x 1
	Ethernet	10/100 Base-T x 1	10/100 Base-T x 1	10/100 Base-T x 1
	COM Port	COM1: RS-232/RS-485 2W/4W COM3: RS-485 2W	COM1: RS-232 4W, COM2: RS-485 2W/4W	Con.A: COM2 RS-485 2W/4W, COM3 RS-485 2W Con.B: COM1 RS-232 4W, COM3 RS-232 2W*
RTC		Built-in	Built-in	Built-in
Power	Input Power	24±20%VDC	24±20% VDC	24±20%VDC
	Power Isolation	Built-in	Built-in	Built-in
	Power Consumption	350mA@24VDC	450mA@24VDC	510mA@24VDC
	Voltage Resistance	500VAC (1 min.)	500VAC (1 min.)	500VAC (1 min.)
	Isolation Resistance	Exceed 50MΩ @ 500VDC	Exceed 50MΩ @ 500VDC	Exceed 50MΩ @ 500VDC
Specification	PCB Coating	N/A	N/A	N/A
	Enclosure	Plastic	Plastic	Plastic
	Dimensions WxHxD	128 x 102 x 32 mm	200.4 x 146.5 x 34 mm	271 x 213 x 36.4 mm
	Panel Cutout	119 x 93 mm	192 x 138 mm	260 x 202 mm
	Weight	Approx. 0.25 kg	Approx. 0.52 kg	Approx. 1 kg
	Mount	Panel mount	Panel mount	Panel mount
Environment	Protection Structure	NEMA4 / IP65 Compliant Front Panel	NEMA4 / IP65 Compliant Front Panel	NEMA4 / IP65 Compliant Front Panel
	Storage Temperature	-20° ~ 60° C (-4° ~ 140° F)	-20° ~ 60° C (-4° ~ 140° F)	-20° ~ 60° C (-4° ~ 140° F)
	Operating Temperature	0° ~ 55° C (32° ~ 131° F)	0° ~ 55° C (32° ~ 131° F)	0° ~ 55° C (32° ~ 131° F)
	Relative Humidity	10% ~ 90% (non-condensing)	10% ~ 90% (non-condensing)	10% ~ 90% (non-condensing)
	Vibration Endurance	10 to 25Hz (X, Y, Z direction 2G 30 minutes)	10 to 25Hz (X, Y, Z direction 2G 30 minutes)	10 to 25Hz (X, Y, Z direction 2G 30 minutes)
Certificate	CE	CE marked	CE marked	CE marked
	UL	N/A	N/A	N/A
Software	Weincloud	EasyAccess 2.0 (Optional)	EasyAccess 2.0 (Optional)	EasyAccess 2.0 (Optional)

The Product's colors printed in this brochure may differ from those of the actual product.

All information contained in this brochure is subject to change without notice.

Other company names and product names in this document are the trademarks or registered trademarks of their respective companies.

\* MT8106iP: Only Tx & Rx (no RTS/CTS) may be used for COM1 RS-232 when COM3 RS-232 is also used.



## Taiwan

Tel: +886-2-22286770  
Fax: +886-2-22286771

Address: 14F., No. 11, Qiaohe Rd., Zhonghe Dist.,  
New Taipei City 235029, Taiwan (R.O.C.)

Website: [www.weintekiiot.com](http://www.weintekiiot.com)  
Sales: [salesmail@weintek.com](mailto:salesmail@weintek.com)  
Product Support: [servicemail@weintek.com](mailto:servicemail@weintek.com)

    **RoHS** ISO 9001:2015

ENG / 2023.08.09